





LOW, STREAMLINED AND ROUNDED

All PERFECT rotary mowers comply with the highest level of current requirements in modern orchards and vineyards. In order to prevent damage to low hanging branches and fruit our T-models have a low, streamlined profile and round sides.

All generously overlapping cutting blades are driven indirectly by means of V-belts, mostly with automatic springloaded belt tensioners. This flexible drive system protects the gearbox from shock loads.

TI





T SERIES

Extra low orchard models



Either one or two front support wheels and rear rollers give the necessary stability and excellent terrain adjustment. loads.



Tmodels can be equipped with a unique "Perfect" mow-spray frame that has been designed so that both the front and the rear of the mower is able to move freely from the headstock.



EXTRA'S

- Swing away blades
- "Perfect" pulling type headstock for front mount
- Double headstock for front and rear mount
- Mow-spray combination feature

TECHNICAL SPECIFICATIONS	T-155	T-180	T-200	T-225	T-250	T-290
Cutting width (cm/inch)	155 / 5'2"	180 / 5'11"	200 / 6'7"	225 / 7'5"	250 / 8'2"	290 / 9'6"
Min. power required						
at 50 rpm of pto (kW/HP)	16/22	18 /25	22 / 30	26 / 35	29 / 40	33 / 45
Number of blades	3	3	3	3	3	3
Total width (cm/inch)	160 / 5'3"	185 / 6'1"	205 / 6'9"	230 / 7'7"	255 / 8'4"	295 / 9'8"
Cutting height (cm/inch)	4-10 / 1½-4	4-10 / 1½-4	4-10 / 1½-4	4-10 / 1½-4	4-10 / 1½-4	4-10 / 1½-4
Length of rear roller (cm/inch)	(1) 102 / 40"	(2) 38 / 15"	(2) 48 / 19"	(2) 53 / 21"	(2) 53 / 21"	(2) 53 / 21"
Weight (kg/lbs)	350 / 772	385 / 849	415 / 915	500 / 1102	525 / 1157	535 / 1179

As our policy is one of continuous improvement, we reserve the right to change the specification or to modify the desing without prior notice

