





BRUSH SWEEEPERS FOR PRUNINGS AND LEAFS

PERFECT brush sweepers are designed to remove the prunings and leaf residues which are in the tree or vine rows and to clean the herbicided strips in order to discourage the development of fungus and to implement an optimal chemical weed control.

They are driven by a hydraulic motor and are equipped with elastic and highly resistant sweeper brushes which spin at approximately 150 rpm. Working width 100 cm.

11



MODEL SPA & SPF

Single brush sweepers



The sweeper head position is adjustable both in working angle and in working height, which assures a high quality working result in all conditions.

For perfect terrain adjustment the sweeper head is supported by a swivel wheel.



The SPF front mounted models are equipped with a carriage beam for fix mounting to the front of a tractor. A headstock for attachment to the tractor 3-pt front linkage is optionally available.

MODEL SPA & SPF

Model SPA is for attachment to a flail chopper/shredder and comes with a mounting plate

Model SPF is for attachment to the front of a tractor and comes with carriage beam



EXTRA'S

- · Rubber flaps instead of standard brushes
- Hydraulic lift ram
- Hydraulic width adjustment
- Working width 58 cm (Vineyards)
- Working width 130 cm
- Head stock for front and 3-pt. linkage (only model SPF) Complete with width adjustment

TECHNICAL SPECIFICATIONS	SPA	SPF
Sweeper width (cm/inch)	100 / 3'3"	100 / 3'3"
Necessary oil flow I/min.	30	30
Necessary oil pressure Bar/PSI	± 70 / 1015	± 70 / 1015
Necessary hydraulic couplings	1 x double	1 x double
on the tractor	acting or 1	acting or 1
	single acting	single acting
	and 1 free flow	and 1 free flow
	return	return

As our policy is one of continuous improvement, we reserve the right to change the specification or to modify the desing without prior notice

